

Pneumatic Torque Wrench Reversible non-Impacting A *Controlled Bolting Solution*

34", 1" & 1½" Square Drives offer Smooth Continuous Rotation from 200 ft lbs to 11,500 ft lbs Most advanced **Planetary Gear** reduction Gearbox driven by a precision air motor.

RAD

Precision Spline gives 360° reaction arm placement & nose extension control.

Automatic 2 Speed gearbox Models for high-speed rundown and single sequence precision tightening.

Reaction Arm Range adaptable to every situation.

> Low Noise, High Power-to-Weight ratio reducing operator strain. 88x less vibration than Rattle Guns with Zero hammering!

Simple Pistol Grip Trigger & Reverse Switch operation

Unmatched Power & Reliability capable of accuracy of +/-5%, & repeatability of +/-2%.



Complete with: Cradle + Hose Regulator + Lubricator Range covers **Pneumatic, Electronic, Electric, and Battery powered** Tools offering a complete solution











Pneumatic Torque Nutrunner

Fast - Non Impacting - Accurate - Ultra Low Vibration - Simple to Use - Quiet



Part Number	Model	Sq Drive	Torque Ft Lbs	Torque Nm	RPM	Weight
12316	350SL	3/4"	50 -350	70 - 475	65	2.7 kg
12814	7GX	3/4"	100 -700	130 - 950	30	3.6 kg
12818	10GX	3/4"	200 -1000	270 - 1,350	20	3.6 kg
17328	15DX	1"	300 -1,500	400 - 2,000	15	5.6 kg
12377	25GX	1"	500 -2,500	700 - 3,400	8	6.1 kg
12356	34GX	1"	1000 -3,400	1,400 - 4,600	12	9.0 kg
12357	50	1-1/2"	1,500 -5,000	2,000 - 6,800	7	12.7 kg
15328	60DX	1-1/2"	2,000 -6,000	2,700 - 8,130	6.6	12.7 kg
18558	80DX	1-1/2"	2500 - 8,000	3,400 - 10,800	4.2	13.6 kg
12383	85GX	1-1/2"	3000 -8,500	4,070 - 11,520	4.5	17.4 kg

RAD Air Nut Runners -Perfect solution for accurate, repeatable torque.

RAD Pneumatic Torque Tools use standard workshop 100PSI air at 30 cfm. Simply adjust the air regulator to set Torque Value - The tool will stall when correct torque is reached.





Pneumatic Wrench NX Tool Kits



RAD NX Kits come with

3 Reaction Arms + Nose Extension covering Multiple Applications of high torque bolting





NX Tool Kit Models

Part	Tool	Torque		Speed	Nose
Number	Model	Ft.lbs	NM	RPM	Extension
15517	7GX-NX	100-700	135-950	30	12"
13691	10GX-NX	200-1000	270-1350	20	12"
15518	1400NG-NX	300-1400	400-1900	15	12"
15519	1400NG-2-NX	500-1400	700-1900	69	12"
15520	1800NG-NX	500-1800	700-2450	10	12"
15521	1800NG-2-NX	700-1800	950-2450	53	12"
15522	25GX-NX	500-2500	700-3400	8	18"



Complete with : Cradle + Hose + Regulator + Lubricator

Comes in tough dustproof / waterproof case

Accuracy - +/- 5% Reduced Noise Levels - 80 db.

Non Impacting: Zero Hammering or Vibration

High RPM : Reduce Bolting time

Controlled Torque : Smooth Continuous Flow from 100 to 2500 ft lbs









1/2 your time on common maintenance tasks!

Packaging your RAD Tool of choice with a Nose Extension & 3 Reaction Arms covers every bolting applications

Distributed by: HIRE TORQUE TOOLS Vic - Ph:03 9710 1386