

GOLD High Torque Sockets

Industrial Quality!

Well exceeds ISO 1711-2
and ASME B 107.2-1995

Perfect Setup!

All sockets are the same length to suit fixed
length reaction arms

Socket Retainers

Each socket is supplied with
the correct Pin and 'O' Ring.

Safety first!

Each socket is stamped with a
safe maximum torque rating

Right socket for the right tool!

All sockets are gold coloured for easy identification

Torque sockets are specifically designed for high
torque applications. They ensure safe operation
with hydraulic wrenches, pneumatic nut runners
and multipliers.



High Torque Socket Sets

METRIC Part no. IM8MHTS **IMPERIAL** Part no. IM8HTS

Contents. As per table



1" Drive


Order No.	Size	D2	D1	L2	L	METRIC sets	IMPERIAL sets
6055S030	30	1 3/16	54	51	21	85	
6055S032	32		54	53	22	85	✓
6005S110	1 3/16	54	55	22	85		✓
6055S035	35	1 3/8	54	57	22	85	
6055S036	36		54	58	25	85	✓
6005S114	1 7/16	54	58	25	85		✓
6055S038	38	1 1/2	54	61	25	85	✓
6055S041	41		54	64	27	85	✓
6005S120	1 5/8	54	64	27	85		✓
6055S043	43	1 11/16	54	68	27	85	✓
6055S046	46	1 13/16	54	72	30	85	✓
6005S128	1 7/8	54	73	32	85		✓
6055S048	48		54	74	32	85	
6005S130	1 15/16	58	76	32	85		✓
6055S050	50		58	77	35	85	✓
6005S200	2	58	78	35	85		✓
6055S052	52		58	79	35	85	✓
6005S202	2 1/16	58	79	35	85		
6055S054	54	2 1/8	58	82	35	85	✓
6055S055	55		58	83	35	85	✓
6005S206	2 3/16	58	83	35	85		✓
6005S208	2 1/4	58	86	40	85		✓
6055S060	60		58	89	42	85	✓
6005S212	2 3/8	58	89	42	85		✓
6005S214	2 7/16	58	91	42	85		
6005S216	2 1/2	58	93	42	85		
6055S065	65	2 9/16	58	95	42	85	✓
6055S070	70	2 3/4	58	102	42	85	✓

For Re-ordering

Pin 69734043
O-ring 69745100

Alternative option

Ret-Ring RR10008CG



Distributed by:

Hire TORQUE TOOLS Vic

www.HTTV.com.au 03 9710-1386